
Technical Data Sheet Paint Control Tape

1190

Product Description

JTAPE Paint Control Tape enables the optimisation of paint thickness and coverage. With it's easy to check spray pattern, the product saves on materials, time and improves processes. The product is manufactured from a high quality, printed 80°C automotive grade crepe paper masking tape with excellent adhesion to all surfaces. JTAPE 1180 can be used with all solvent and waterbased paints providing clean removal with no residue.

Product Construction



Shelf Life

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

Carrier	Crepe Paper
Adhesive	Rubber
Ink	Waterbased
Colour	Ivory with black checks
Paper Thickness	90 micron
Total Thickness	132 micron
Width	38mm (+/- 2mm)
Length	28m (+/- 0.5m)

Performance Properties

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	2,7 N/cm
Tensile Strength	50 N/cm
Elongation at break	10%
Temperature Resistance	80°C for 1 hour

Important Notice To Purchaser

JTAPE makes no warranties, express or implied, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluates the JTAPE automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application.

Limitation Of Remedies And Liability

If the JTAPE product is proved to be defective. The exclusive remedy, at JTAPE's option, shall be to refund the purchase price of or to repair or replace the defective JTAPE product. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

