

PRIMESHIELD

A fast and efficient way to mask door apertures and other vehicle gaps making previously unmaskable gaps simple and easy to protect.

PART NO:	SIZE:	UNITS:
1015.1535	15mm x 35m	1
1015.2225	22mm x 25m	1



Primeshield

FEATURES

A fast and efficient way to mask door apertures and other vehicle gaps making previously unmaskable gaps simple and easy to protect. **BENEFITS**

- Dramatically reduces process times
- Seals and protects from overspray
- Precise fingertip adjustment
- Easy to apply self locating
- No primer build up on panel edges
- Reduces material use



JTAPE Limited, Hulley Road, Macclesfield, Cheshire SK10 2SF United Kingdom Tel: +44 (0)1625 618185 Fax: +44 (0)8701 207748 Email: info@jtape.com www.jtape.com

HOW TO USE THIS PRODUCT:



1. Prepare the vehicle before masking.



3. Check to ensure the tape is firmly located in all the gaps.






5. Prime the desired areas.



2. Apply the tape in the gap smaller side first. Locate the tape in the gap so that it sits in the central groove.



4. Prepare the vehicle to be painted.



6. Remove the tape before baking.

JTAPE Limited, Hulley Road, Macclesfield, Cheshire SK10 2SF United Kingdom Tel: +44 (0)1625 618185 Fax: +44 (0)8701 207748 Email: info@jtape.com www.jtape.com