

PRODUCT DESCRIPTION

JTAPE Olive Fine Line Masking Tape uses a thermally stabilised polypropylene backing with a urethane based pressure sensitive adhesive. It is designed for straight line use, adheres to a wide variety of surfaces and will hold and cleanly remove from surfaces in temperatures up to 138°C/280°F for at least 45 minutes. After demasking, it will leave no residue and a sharp, clean separation line. This product meets military specification T-215955D type III.

PRODUCT CONSTRUCTION



SHELF LIFE

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	Embossed Polypropylene
Colour	Olive Green
Adhesive	Pigmented Urethane
Thickness	0.127mm PSTC-33
Width	3mm, 6mm, 9mm, 12mm, 19mm and 25mm (+/- 1mm)
Length	55m (+/- 0.1m)
Other sizes available upon request.	

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Tensile Strength	0.215 kg/mm ASTM D-3759
Elongation at Break	600%
Adhesion to Steel	33.6 g/mm ASTM D-3330
Heat Resistance	138°C for at least 45 minutes

JTAPE LIMITED

Hulley Road, Macclesfield, Cheshire, SK10 2SF, United Kingdom

Tel: +44 (0)1625 618185 Fax: +44 (0)8701 207748

www.jtape.com Email: info@jtape.com

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: If the JTAPE product is proved to be defective. THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.