

SEAL WRAP

TECHNICAL DATA SHEET **1060**

V3.07/21

PRODUCT DESCRIPTION

JTAPE Seal Wrap is a low tack protection film for both interior and exterior applications. The product consists of self-wound, low density polyethylene film with ultraviolet inhibitor and is coated with a custom formulated water based acrylic adhesive - ensuring no residue is left upon removal.

PRODUCT CONSTRUCTION



SHELF LIFE

One year from date of receipt by customer when stored at 25°C ±10°C (77°F ±18°F) and 60% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	Polyethylene-based film
Adhesive	Pressure-Sensitive Acrylic
Colour	Clear
Thickness	50µm / 0.050mm (±0.01mm)
Width	Various options: 300mm, 600mm and 900mm
Length	50m

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	1.35N/cm (±0.2)
Elongation at Break	>200%
Temperature Range	15±°C to 35°C (59°F to 95°F) at <80% relative humidity

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.