
# PRODUCT DESCRIPTION

**JTAPE** Double Sided Mounting Tape has a high tack permanent adhesive with excellent ageing and weather resistant properties for automotive emblems, decals, mouldings and mirror fixings. The product also has a good resistance to solvents, chemicals, UV and heat.

#### PRODUCT CONSTRUCTION



## **SHELF LIFE**

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

## PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	High Performance PE Foam (96kg/m³) Black
Liner	Green Polyolefin
Adhesive	Acrylic (Solvent Based)
Thickness	0.8mm (+/- 0.05mm)
Width	9mm, 12mm, 19mm and 25mm (+/- 1mm)
Length	10m (+/- 0.1m)
Other sizes av	railable upon request.

## PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	PSTC-3 1.8kg/25mm
Shear Strength	PSTC-7 over 24 hours with 2kg on 25mm x 25mm at 23°C
Tensile Strength	Over 45kgs/25mm x 25mm
Heat Resistance	PSTC-9 over 24 hours with 0.5kg on 25mm x 25mm at 80°C
Tack	J. Dow Number 20

### **JTAPE LIMITED**

Hulley Road, Macclesfield, Cheshire, SK10 2SF, United Kingdom Tel: +44 (0)1625 618185 Fax: +44 (0)8701 207748

www.jtape.com Email: info@jtape.com

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application.

Limitation of Remedies and Liability: If the JTAPE product is proved to be defective. THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.