

DOUBLE SIDED MOUNTING TAPE

TECHNICAL DATA SHEET **2106**
V3.12/21

PRODUCT DESCRIPTION

JTAPE Double Sided Mounting Tape is a polyethylene foam tape, coated on both sides with an acrylic-based adhesive with good instant grab. The product has a good working temperature range and excellent adhesion to a wide variety of substrates including plastics & metals; ideal for bonding emblems, decals, mouldings and mirror fixings. The product also has good resistance to solvents, chemicals, UV, cold and heat.

SHELF LIFE

One year from date of receipt by customer when stored at 22°C ±5°C (72°F ±10°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.


Carrier	Polyethylene Foam
Adhesive	Solvent-Based Acrylic
Colour	Black (with Green Release-Liner)
Thickness	0.80mm (±5%)
Width	6mm, 9mm, 12mm, 19mm, 25mm, 50mm (±5%). Other widths available on request.
Length	10m (±0.1). Other lengths available on request.

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	≥10N/cm
Elongation at Break	≥180%
Tensile Strength	≥9N/cm
Temperature Range	-20°C to +80°C / -4°F to 175°F

PRODUCT CONSTRUCTION



Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.