


# PREMIUM CLOTH PROTECTION TAPE - RED

TECHNICAL DATA SHEET **2201**  
V3.07/21

## PRODUCT DESCRIPTION

JTAPE Premium Cloth Tape is a polyethylene cloth laminate adhesive tape with a waterproof high tack adhesive. As a premium duct-tape it can be used in the automotive, marine, industrial, construction and DIY sectors. Specially formulated to allow clean removal after use not leaving any adhesive residue. Available in 5 different colours: Black (2203), Silver (2202), Red (2201), Blue (2208) & White (2200). Various widths available on request.

## PRODUCT CONSTRUCTION



## SHELF LIFE

6 months from date of receipt by customer when stored at 20°C ±5°C (68°F ±9°F) and 60% relative humidity.

## PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	Release-coated polyethylene film with high-grade cloth
Adhesive	Natural Rubber/Resins
Colour	White (2200), Red (2201), Silver (2202), Blue (2208), Black (2203)
Thickness	0.30mm (±0.05mm)
Width	50mm (±5%). Other widths available on request.
Length	50m (±0.2m). Other lengths available on request.

## PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	3.9N/cm (±0.5)
Elongation at Break	10%
Tensile Strength	50N/cm
Temperature Range	Recommended application temperature: 5°C/41°F to 35°C/95°F. Max. working temperature 40°C

Tel: +44 (0)1625 618185 | [www.jtape.com](http://www.jtape.com) | [info@jtape.com](mailto:info@jtape.com)

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.