
LOGO TAPE **PART NO. 2210**

DIRECTIONS FOR USE:



STEP 1

Mask around the surrounding area to make a guide template.



TAPE

TAPE

TAPE

TAPE

7TAPE



STEP 4

Remove the excess foam backing from the vehicle, then panel wipe in preparation for badge replacement.



STEP 7

Replace guide template, then replace badge to original position, applying pressure to secure.






STEP 8

Remove guide template and tape from badge.



For more information call +44 (0)1625 618185 or Email info@jtape.com

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and vironmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE ive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective. THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability







AREAS OF APPLICATION

Logos Decals Badges

STEP 2

ZTAT

Tape the badge to keep the letter and numbers together and apply pressure, then remove the guide template.

STEP 5

Pull away printed liner to expose adhesive and apply badge to the adhesive.



STEP 3

Use fine cheese wire to remove badge, leaving as much of the existing foam backing on the back of the badge as possible.



STEP 6

Turn over and apply pressure to the back of the badge. Then pull printed liner away and carefully remove badge.

www.jtape.com