

# BREATHABLE MASKING FILM

## TECHNICAL DATA SHEET **1080.5012**

V3.06/21

### PRODUCT DESCRIPTION

JTAPE Breathable Masking Film is a high-density polyethylene film suitable for use on interior and exterior applications. The product consists of a self-wound, folded, co-extruded custom polyethylene film, full-side corona treated to hold mist and general paintoverspray of both solvent and waterborne paints during the spraying process. Prevents water condensate build-up due to its breathable characteristic.

### PRODUCT CONSTRUCTION



### SHELF LIFE

12 months from date of receipt by customer when stored at 20°C ±5°C (68°F ±9°F) and 60% relative humidity.

### PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Corona-treated Polyethylene film
Adhesive	N/A - Non-Adhesive Film
Colour	Green (Translucent)
Breathable	Yes - reduces moisture build-up
Thickness	17µm / 0.017mm (±5%)
Width	5m ±5%
Length	120m ±10%

### PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Temperature Resistance	Up to 110°C (210°F)
------------------------	---------------------

Tel: +44 (0)1625 618185 | [www.jtape.com](http://www.jtape.com) | [info@jtape.com](mailto:info@jtape.com)

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

**#TAPESMART**

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective. THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.