

HS CLEAR DOUBLE-SIDED ACRYLIC TAPE


TECHNICAL DATA SHEET 2109

V3.07/21

PRODUCT DESCRIPTION

JTAPE High Strength Clear Acrylic Tape is a reinforced 1.0mm acrylic foam tape with very high-tack, maximum performance acrylic adhesive. High Strength Clear Double-Sided Acrylic Tape has an excellent resistance to solvents, chemicals, UV and heat; enabling the tape to bond permanently to an extensive range of substrates. This clear tape's high-strength adhesive makes it ideal for bonding signs, emblems, nameplates; metal, glass and most plastics.

PRODUCT CONSTRUCTION



SHELF LIFE

One year from date of receipt by customer when stored at 30°C ±8°C (86°F ±15°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	Clear Acrylic Foam
Adhesive	Acrylic adhesive integral to foam
Colour	Clear (with Red HDPE Release-Liner)
Thickness	1.00mm (±0.10mm)
Width	Various options: 3mm, 6mm, 9mm, 12mm, 19mm, 25mm (±5%). Other widths available on request.
Length	10m (±0.2m) as standard. Other lengths available on request.

PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	12N/cm (±3) (180° S/Steel)
Temperature Range	high and low temperature-stable
Dynamic Shear	120N (Stainless Steel, 25mm ²)

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.