

# GREEN HIGH TEMPERATURE POLYESTER FILM DISCS (220°C)

**TECHNICAL DATA SHEET** 4009  
V3.10/21

## PRODUCT DESCRIPTION

Green High Temperature Polyester Film Discs are resistant to temperatures up to 220°C. They are specifically designed to cover the rear hub of alloy wheels and to provide a reliable solution while coating, baking and treating wheels during the refurbishment process. High Temperature Crepe Masking Discs are also available in a 160°C temperature resistant crepe-tape version – Product Ref 4003.

## PRODUCT CONSTRUCTION



## SHELF LIFE

One year from date of receipt by customer when stored at 22°C ±5°C (68°F ±9°F) and 50% relative humidity.

## PHYSICAL PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Carrier	Polyester Film
Adhesive	Silicone-based
Colour	Green (Translucent)
Thickness	80µm / 0.080mm (±5%)
Release Liner	Release-coated PET Film Liner
Sizes	Ø155mm. Other sizes/diameters available on request.
Quantity	250 discs per roll

## PERFORMANCE PROPERTIES

Values shown are typical values and not to be used for specification purposes.

Peel Adhesion	≥3N/cm
Elongation at Break	≥100%
Temperature Resistance	up to 220°C/428°F (≥30 minutes)

Tel: +44 (0)1625 618185 | [www.jtape.com](http://www.jtape.com) | [info@jtape.com](mailto:info@jtape.com)

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

**#TAPESMART**

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.