PRIME & PAINT FOAM MASKING TAPE

TECHNICAL DATA SHEET 1016

V3.1 (11/26)

PRODUCT DESCRIPTION

Prime & Paint Foam Masking Tape is a 2-in-1 solution for masking door apertures to stop the ingress of paint during the automotive finishing process. Leaves a soft edge and offers clean, residue-free removal.

PRODUCT CONSTRUCTION



SHELF LIFE

12 months from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Material	Polyurethane Foam
Adhesive	Thermoplastic Synthetic Rubber
Colour	White
Thickness	8mm (±15%)
Width	35mm (±15%)
Length	30m (±5%)

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	3N (≈9N/25mm)	[ASTM D3330-F]
Elongation at Break	≥250%	[ISO 1798]
Tensile Strength	≥160kPa	[ISO 1798]
Density	27kg/m³	[ISO 845]
UV Resistance	Limited	
Temperature	≤85°C (185°F) for ≤1	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for the user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.