

PRIMESHIELD

TECHNICAL DATA SHEET 1015

V3 (08/23)

PRODUCT DESCRIPTION

JTAPE Primeshield is designed for masking door apertures during the priming process, protecting panel edges from a build-up of primer.

Available in two sizes:

(1015.1535): 15mm wide x 35m

(1015.2225): 22mm wide x 25m

SHELF LIFE

12 months from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.


	1015.1535	1015.2225
Material	Foam	Foam
Adhesive	None	None
Colour	White	White
Thickness	10mm (±10%)	13mm (±10%)
Width	15mm (±10%)	22mm (±10%)
Length	35m (±0.5m)	25m (±0.5m)

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	N/A	N/A
Elongation at Break	≥250%	≥250%
Tensile Strength	≥16N/cm	≥16N/cm
Density	27kg/m ³ (±4kg/m ³)	27kg/m ³ (±4kg/m ³)
UV Resistance	Limited	Limited

PRODUCT CONSTRUCTION



Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.