

STRIPING TAPE

TECHNICAL DATA SHEET 1118

V3 (01/25)

PRODUCT DESCRIPTION

JTAPE Striping Tape uses a thermally stabilised, embossed polypropylene carrier with a polyurethane-based pressure sensitive adhesive. The product performs in temperatures up to 120°C for 60 minutes - leaving sharp, clean separation lines and offers good solvent resistance. The product has 8 pre-cut strips making it ideal for striping straight lines / pin-strips in a variety of configurations.

SHELF LIFE

12 months from date of receipt by customer when stored at 25°C ±5°C (77°F ±9°F) and 65% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Medium-low opacity, Embossed PP
Adhesive	PU
Colour	Olive Green
Total Thickness	150µm / 0.150mm (±10%)
Width	25mm ± 1mm (i.e. 8x 1.5mm strips + 2x 6.5mm edge-strips (±5%))
Length	14m (±2%)

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	8.2N/25mm	[ASTM D-3330]
Elongation at Break	700%	
Tensile Strength	22N/cm	[ASTM D-3759]
Temperature Range	-40°C to 120°C (-40°F to 248°F)	
Application Temperature	10°C to 49°C (-50°F to 120°F)	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.