

CUSTOMISING TAPE

TECHNICAL DATA SHEET 1119

V4 (01/25)

PRODUCT DESCRIPTION

JTAPE Customising Tape uses a thermally stabilised PVC backing with a rubber-based pressure sensitive adhesive. The product has 8 strips of pre-cut fine line masking tape - allowing a multitude of curved patterns to be created when customising. It is highly flexible, easy to curve and will hold and cleanly remove from surfaces in temperatures up to 150°C/302°F for at least 1 hour. After demasking, it will leave no residue and a sharp, clean separation line.

PRODUCT CONSTRUCTION



SHELF LIFE

12 months from date of receipt by customer when stored at 20°C ±10°C (68°F ±18°F) and 60% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	PVC
Adhesive	Rubber-based
Colour	Green
Thickness	150µm / 0.150mm (±10%)
Width	8 x 1.5mm (1/16") strips giving total width of 12mm
Length	10m (±2%)

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	6.5N/25mm	[ASTM D-1000]
Elongation at Break	>100%	
Tensile Strength	22N/cm	
Temperature Resistance	up to 150°C (302°F) for 1 hour	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART