

DUO MASKING TAPE


TECHNICAL DATA SHEET 1150

V3 (02/25)

PRODUCT DESCRIPTION

DUO Masking Tape is a high-performance, automotive-grade crepe masking tape, designed to mask a variety of areas around a vehicle. Consisting of a dual-facing adhesive surface, a PET tab and release liners to make the product as versatile and usable as possible. The product can be used with all water and solvent-based paints and will hold to and cleanly remove from various surfaces including metals, plastics, rubbers and trims and offers clean, residue-free removal even when exposed to temperatures up to 80°C for up to 30 minutes.

PRODUCT CONSTRUCTION



SHELF LIFE

12 months from date of receipt by customer when stored at 20°C (68°F) and below 65% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Crepe paper
Adhesive	Rubber-based with resins
Colour	Natural/Beige
Film	PET
Liners	HDPE
Total Thickness	295µm / 0.295mm (±5%)
Width	75mm (±5%)
Length	20m (±2%)

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	5.8N/25mm	[ASTM D1000]
Elongation at Break	≥8%	
Tensile Strength	≥200N	[ISO527-1]
Temperature Resistance	≤80°C (176°F) for ≤30 min. hour	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.