

GREY DOUBLE-SIDED ACRYLIC TAPE


TECHNICAL DATA SHEET 2110

V5 [11/24]

PRODUCT DESCRIPTION

JTAPE Grey Double-Sided Acrylic Tape is a reinforced acrylic foam tape with acrylic adhesive on both sides. It provides very high initial grab and long-term tack with excellent shear strength performance. The product has an excellent working temperature range and superb adhesion to a wide variety of substrates including LSE and MSE plastics and metals both untreated and painted. Ideal for bonding emblems, nameplates, plastic panels and metals.

PRODUCT CONSTRUCTION



SHELF LIFE

12 months from date of receipt by customer when stored at 20°C ±5°C (68°F ±9°F) and 60% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Acrylic Foam
Adhesive	Solvent-based Acrylic
Colour	Grey (with Red HDPE Release-Liner)
Thickness	1.10mm (±5%)
Width	3mm, 6mm, 9mm, 12mm, 19mm, 25mm (±5%). Other widths available on request.
Length	5m or 10m (±2%).

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	20 mins.: 68N/25mm / 24 hrs: 115N/25mm / 72 hrs: 125N/25mm	[ASTM D-3330: F]
Elongation at Break	750%	
Tensile Strength	175N/cm (SUS: 50mm/min; 25mm², 24hr)	[ASTM D-897]
Dynamic Shear	540N (SUS 50mm/min; 25mm²)	[ASTM D-1002]
Static Shear	>10,000min. 1000g @ 110°C (25mm²)	[ASTM D-3654]
Temperature Range	-40°C to 180°C (-40°F to 356°F)	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective. THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.