

# SEAM SEALING TAPE

## TECHNICAL DATA SHEET 2205

V4 [02/25]

#### PRODUCT DESCRIPTION

JTAPE Seam Sealing Tape is a reinforced, 1.0mm acrylic foam tape with very high-tack and excellent shear strength and a high performance acrylic adhesive. Seam Sealing Tape has excellent resistance to moisture, chemical, UV and heat; making the tape bond securely to a wide range of surfaces. Ideal for replacing seams on automotive doors and flanges, etc.

PRODL	CT	CON	STRU	CTION	

Liner —	
Adhesive —	
Carrier —	

#### **SHELF LIFE**

24 months from date of receipt by customer when stored at 30°C ±8°C (86°F ±15°F) and 50% relative humidity.

#### PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Acrylic Foam
Adhesive	Acrylic adhesive integral to foam
Colour	Translucent (with white liner)
Thickness	1.00mm (±0.10mm)
Liner	White, release-coated paper
Width	9mm or 12mm (±5%). Other widths available on request.
Length	10m (±0.2m) as standard. Other lengths available on request.

### PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	49N/25mm	[ASTM-D3330]
Dynamic Shear	68N/cm² (S/Steel @ 200mm/min)	[ASTM-D1002]
Temperature Resistance	120°C (248°F) for ≤4 hrs / 93°C (199°F) for ≤7 days	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

**#TAPESMART**