

SEAM SEALING TAPE


TECHNICAL DATA SHEET **2205**

V4 [02/25]

PRODUCT DESCRIPTION

JTAPE Seam Sealing Tape is a reinforced, 1.0mm acrylic foam tape with very high-tack and excellent shear strength and a high performance acrylic adhesive. Seam Sealing Tape has excellent resistance to moisture, chemical, UV and heat; making the tape bond securely to a wide range of surfaces. Ideal for replacing seams on automotive doors and flanges, etc.

PRODUCT CONSTRUCTION



SHELF LIFE

24 months from date of receipt by customer when stored at 30°C ±8°C (86°F ±15°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Acrylic Foam
Adhesive	Acrylic adhesive integral to foam
Colour	Translucent (with white liner)
Thickness	1.00mm (±0.10mm)
Liner	White, release-coated paper
Width	9mm or 12mm (±5%). Other widths available on request.
Length	10m (±0.2m) as standard. Other lengths available on request.

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	49N/25mm	[ASTM-D3330]
Dynamic Shear	68N/cm ² (S/Steel @ 200mm/min)	[ASTM-D1002]
Temperature Resistance	120°C (248°F) for ≤4 hrs / 93°C (199°F) for ≤7 days	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.