

# DOOR SKIN REPLACEMENT FILM

## TECHNICAL DATA SHEET 2206

V3 [02/25]

DDNNI	ICT	DESCR	IDTINN
LUODI	JLI	DEJUN	IT HUN

Door Skin Replacement Film is a polyethylene based clear film for making door interiors watertight. The product is ideal for replacing door skin membranes when used with JTAPE Refit Tape (2207). Just cut to size, add the refit tape to the door and then position the film to seal the open area.

PRODUCT CONSTRUCTION					
Film		_			

#### SHELF LIFE

12 months from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

#### PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Polyethylene
Adhesive	None
Colour	Clear (Translucent)
Thickness	125μm / 0.125mm (±10%)
Width	600mm (±5%)
Length	50m (±10%)

### PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Elongation at Break	15%
Tensile Strength	25N/cm
Temperature Range	-40°C to 90°C (-40°F to 194°F)
Application Temperature	-10°C to 40°C (-14°F to 104°F)

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective. THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REPLASE PRICE OF OR TO REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.