

CLEAR LOGO TAPE

TECHNICAL DATA SHEET 2210


V3 [02/25]

PRODUCT DESCRIPTION

Clear Logo Tape is a permanent carrier-free transfer-adhesive with an instant aggressive bond. The product has been specifically designed for the re-application of plastic and metal logos and emblems to all types of vehicles. Logo Tape also performs exceptionally well when exposed to weathering and provides a more consistent application when compared to liquid glues/adhesives and at 0.04mm thick, with no base-carrier provides a better surface to surface bond without a noticeable gap between the surfaces.

PRODUCT CONSTRUCTION

Printed Liner —
Adhesive —
Liner —



SHELF LIFE

12 months from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	None
Adhesive	Solvent-Based Acrylic
Colour	Translucent (with white liner & printed liner)
Adhesive Thickness	40µm (0.04mm) ±10%
Printed Liner	85µm (0.085mm) ±10%, White CCK silicone-coated with printed logo
Liner	100µm (0.10mm) ±10%, White glassine silicone-coated
Width	60mm (±5%).
Length	300mm (±10%).

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	28N/25mm	[ASTM-D3330:F]
Temperature Range	-40°C to 170°C (-40°F to 338°F) ≤1 hr.	
Application Temperature	-10°C to 35°C (14°F to 95°F)	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.