

# WINDSCREEN REMOVAL WIRE

## TECHNICAL DATA SHEET 2211/

V2 [02/25]

### PRODUCT DESCRIPTION

Windscreen Removal Wire is manufactured to the highest quality and specially designed to cut through urethane bonding, commonly found around windscreens. It is composed of three super-strong steel wires that are brassplated to prevent corrosion and aid with cutting, which are braided together to form a single, multi-stranded wire.

#### PRODUCT CONSTRUCTION



#### SHELF LIFE

24 months from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

#### PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Wire Size	3x Ø0.4mm (0.125mm² CSA) ±5% / Total Ø0.88mm (0.375mm² CSA) ±5%
Wire Material	Steel
Wire Coating	Brass
Length	22.5m (±10%). Other lengths available on request.

#### PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Tens	sile Strenath	≥800N

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART