

WINDSCREEN REMOVAL WIRE

TECHNICAL DATA SHEET **2211**


V2 (02/25)

PRODUCT DESCRIPTION

Windscreen Removal Wire is manufactured to the highest quality and specially designed to cut through urethane bonding, commonly found around windscreens. It is composed of three super-strong steel wires that are brass-plated to prevent corrosion and aid with cutting, which are braided together to form a single, multi-stranded wire.

PRODUCT CONSTRUCTION

Wire



SHELF LIFE

24 months from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Wire Size	3x \varnothing 0.4mm (0.125mm ² CSA) \pm 5% / Total \varnothing 0.88mm (0.375mm ² CSA) \pm 5%
Wire Material	Steel
Wire Coating	Brass
Length	22.5m (\pm 10%). Other lengths available on request.

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Tensile Strength	\geq 800N
------------------	-------------

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.