

PREMIUM YELLOW MASKING TAPE


TECHNICAL DATA SHEET **1183**

V2 (10/25)

PRODUCT DESCRIPTION

JTAPE Premium Yellow Masking Tape offers excellent solvent resistance. The product consists of a yellow high quality crepe paper tape with a rubber-based adhesive. The product additionally features no edge curl, no bleed-through and no wrinkling during the application process, providing clean, residue-free removal even when exposed to temperatures up to 130°C (265°F) for up to 30 minutes.

PRODUCT CONSTRUCTION



SHELF LIFE

12 months from date of receipt by customer when stored at 23°C (73°F) and 60% relative humidity.

PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Carrier	Crepe Paper
Adhesive	Rubber-based
Colour	Yellow
Thickness	165µm / 0.165mm (±10%)
Width	18mm (3/4"), 36mm (1 1/2"), 48mm (2") (±5%)
Length	55m (180') (±2%)

PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

Peel Adhesion	9N/25mm	[ASTM-D3330]
Elongation at Break	12%	
Tensile Strength	35N/cm	
Temperature Resistance	130°C (265°F) for ≤30mins	

Tel: +44 (0)1625 618185 | www.jtape.com | info@jtape.com

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The user is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for the user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. **Limitation of Remedies and Liability:** If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.